

Realizing High-accuracy Cutting with a Built-in Motor Spindle

CNC  Spindle  Slide Precision Lathe

J-WAVE PLUS

Make use of dead space for mass production!

Surprisingly compact thanks to incorporation of a 4-inch, gang type, built-in motor spindle!! A machine with advanced functions specialized in small part production makes its debut.



※The image shows the loader equipped machine.

Machine Specifications

Item		Unit	J-WAVE PLUS
Capacity	Optimum turning diameter	mm	φ30
	Max. turning diameter	mm	φ170
	Max. turning length	mm	175
	Chuck size	inch	Collet, 4
	Max. swing over bed	mm	φ380
Spindle	Spindle nose	JIS	A ₂ -4
	Spindle bearing I.D.	mm	φ65
	Through-hole on spindle	mm	(φ20)
	Spindle speed	min ⁻¹	Max.4,500
Tool post	Type		Gang type
	Tool shank	mm	□20
	Boring holder I.D.	mm	φ25
	Max. stroke	mm	X:200 Z:250
	Rapid traverse rate	m/min	X:18 Z:18
Motors	Spindle motor	kW	AC5.5/3.7
	Feed motor	kW	X:AC0.75 Z:AC0.75
	Coolant motor	kW	AC0.18
	Hydraulic motor	kW	(AC0.75)
Size	L×W×H	mm	1,308×1,250×1,395 (780×1,780×1,700*)
	Machine weight	kg	1,500 (1,700*)
Total electric capacity		KVA	12

*When the loader is mounted.

() : Option

Standard Accessories

- Boring holder..... 1 set
- O.D. holder..... 1 set
- Collet flange..... 1 set
- Air solid chucking cylinder..... 1 set
- Thread cutting unit
(Including constant surface speed control) ... 1 set
- Service tool kit..... 1 set
- TAKAMAZ instruction manual ... 1 set

Optional Accessories

- Tool holders
- Collet chucks
- Hydraulic chucks
- Hydraulic unit (With a separate tank)
- TAKAMAZ loader system
- Spindle indexing device (Electric)
- Chip conveyor*1
(Floor type/Spiral type)
- Front air blower
- Rear coolant unit
- Tool post air blow/coolant
- Coolant unit (100 lit.)
- Signal light (1-color/2-color/3-color)
- Automatic fire extinguisher
- Automatic power shut-off device
- Special color
- Others*2

*1 Can only be installed at the rear with the loader specification and at the left side with the standard specification.

*2 For more information on attachments, consult our sales representative.

Controller Specifications

Item	TAKAMAZ & MITSUBISHI M80
Controlled axes	2 axes (X, Z)
Simultaneously controllable axes	Simultaneous 2 axes
Least input increment	0.001mm(X in diameter)
Least command increment	X:0.0005mm Z:0.001mm
Auxiliary function	M-code 3 digit
Spindle function	S-code 4 digit
Tool function	T-code 2 digit
Tape code	EIA (RS232C) / ISO (840) automatic recognition
Cutting feedrate	1~5,000mm/min
Command system	Incremental/Absolute
Linear interpolation	G01
Circular interpolation	G02, G03
Cutting feedrate override	0~150%
Rapid traverse override	F0, 100%
Program number	Program file name 32 characters
Backlash compensation	0~9999μm
Program memory capacity	500Kbyte (1,280m)
Tool offsets	99 sets
Registered programs	1,000 pcs.
Tool geometry/Wear offset	Standard
Canned cycle	G90, G92, G94
Background editing	Standard
Direct drawing dimension programming	Standard
Custom macro	Standard
Nose R compensation	G40, G41, G42
Inch/Metric conversion	G20/G21
Programmable data input	G10
Multiple repetitive cycle	G71~76
Multiple repetitive cycle II	Pocket-shaped
Canned drilling cycle	Standard
Chamfering/Corner R	Standard
Constant surface speed control	G96, G97
Variable lead thread cutting	G34
Clock function	Standard
Alarm history display	512 sets
Sub-program call	up to 8 loops
Decimal point input	Standard
2nd reference point return	G30
Work coordinate system setting	G50, G54~59
Stored stroke check	Standard
Input/Output interface	SD card, USB Flash Memory, Ethernet
Graphic trace	Standard
Graphic check	Standard
Tool life management	Standard
Multiple M codes in one block	Max. 3
Set of Instruction Manuals for Control Device	CD-ROM

Optional Specifications

Spindle orientation
RS232C

- If you modify the machine or replace the loader yourself, our after-sales service may not be available.



TAKAMATSU MACHINERY CO., LTD.

■ HEAD OFFICE & PLANT
1-8 ASAHIGAOKA HAKUSAN-CITY ISHIKAWA JAPAN. 924-8558 TEL +81-(0)76-274-1403 FAX +81-(0)76-274-8530

TAKAMATSU MACHINERY USA INC.

■ CHICAGO HEAD OFFICE
1320 LANDMEIER ROAD ELK GROVE VILLAGE, IL 60007 USA TEL +1-(0)847-981-8577 FAX +1-(0)847-981-8599

■ CINCINNATI OFFICE

5233 MUHLHAUSER ROAD, WEST CHESTER TOWNSHIP, OH 45011 USA TEL +1-(0)513-870-9777 FAX +1-(0)513-870-0325

■ GREENVILLE OFFICE

506 MATRIX PARKWAY PIEDMONT, SC 29673 USA TEL +1-(0)847-981-8577

TAKAMAZ MACHINERY EUROPE GmbH

INDUSTRIEGEBIET, DIEPENBROICH 27 D-51491 OVERATH, GERMANY
TEL +49-(0)2206-919-3960 FAX +49-(0)2206-865-123
TEL +49-(0)2206-866-150

www.takamaz.co.jp

TAKAMAZ MACHINERY (HANGZHOU) CO., LTD.

■ HANGZHOU HEAD OFFICE
NO.6800, JIANGDONG 3RD ROAD, JIANGDONG INDUSTRIAL PARK, XIAOSHAN, HANGZHOU, ZHEJIANG, CHINA
TEL +86-(0)571-8287-9709 FAX +86-(0)571-8215-3732

■ GUANGZHOU OFFICE

ROOM 1316, NO.2, KEHUI FOURTH STREET, NO.99 OF SCIENCE ROAD, LUOGANG DISTRICT, GUANGZHOU
TEL +86-(0)20-8210-9921 FAX +86-(0)20-8210-9921

TAKAMATSU MACHINERY (THAILAND) CO., LTD.

888/59 MOO 9, TAMBOL BANGPLA, AMPHUR BANGPLEE, SAMUTPRAKARN PROVINCE, THAILAND
TEL +66-(0)2-136-7831-3 FAX +66-(0)2-706-4955

TP MACHINE PARTS CO., LTD.

128/345 MOO 1 THEPARAK ROAD BANGSAOTHONG SUBDISTRICT, BANGSAOTHONG DLSTRIC SAMUTPRAKARN 10540
TEL +66-(0)2-706-4514 FAX +66-(0)2-706-4955

PT.TAKAMAZ INDONESIA

JL. FESTIVAL BOULEVARD BLOK AA 11 NO.30.31 GRAND WISATA TAMBUN, BEKASI 17510
TEL +62-(0)21-8261-6431 FAX +62-(0)21-8261-6430

● Distributed by:

Precautions Related to Foreign Exchange and Foreign Trade Control Laws

This product (machine and ancillary equipment) may fall under the category of controlled goods by the foreign exchange and foreign trade control laws.

As such, the exportation must be authorized by the Japanese government as stipulated in the laws

This product is manufactured in accordance with the regulations and standards that prevail in the country or region of destination.

The user must not export, sell, or relocate the product, to any country with different regulations or standards.



This brochure is made from 80% recycled paper.